

Claims

We claim:

- 1 1. A method for increasing transmit diversity gain in a wireless communication
2 system including a transmitter with a plurality of antennas and a receiver with one
3 antenna, comprising:
4 measuring a phase of each of a plurality of signals received by the antenna in
5 the receiver;
6 selecting one of the plurality of signals as a reference signal;
7 determining, independently for each other signal with respect to the
8 reference signal, feedback information indicating a required rotation of each other
9 signal so that a phase of each other signal is within an identical quadrant as the
10 phase of the reference signal;
11 sending the feedback information for each other signal to the transmitter;
12 phase rotating, in the transmitter, each other signal according to the
13 corresponding feedback information to produce a rotated signal; and
14 transmitting the reference signal and each rotated signal to the receiver.
- 1 2. The method of claim 1, in which the reference signal is selected randomly from
2 the plurality of signals.
- 1 3. The method of claim 1, further comprising:
2 measuring a power of each of the plurality of signals; and
3 selecting a highest power signal as the reference signal.

1 4. The method of claim 1, in which the transmitter has two antennas, and the
2 feedback information is one bit.

1 5. The method of claim 4, in which a space encoding vector is $\mathbf{p}_k = [1, (-1)^{b_k}]$, where
2 $b_k \in \{0, 1\}$ is the feedback information sent from the receiver.

1 6. The method of claim 1, in which the transmitter has more than two antennas,
2 and the feedback information is two bits for each other signal.

1 7. The method of claim 6, in which a space encoding vector is
2 $\mathbf{p}_k = \left[1 \quad \exp\left[\frac{i \cdot q_1(k)\pi}{2}\right] \quad \dots \quad \exp\left[\frac{i \cdot q_M(k)\pi}{2}\right] \right]$, where $i^2 = -1$, and $q_m(k) \in \{0, 1, 2, 3\}$ is the
3 feedback information sent from the receiver, for $m = 2, 3, \dots, M$, and $q_1(k) = 0$, for $\forall k$.

1 8. The method of claim 1, further comprising:
2 normalizing the quadrant to the phase of the reference signal.

1 9. The method of claim 8, in which the phases of the other signals with respect to
2 the phase of the reference signal are $\tilde{\theta}_m = \theta_m - \theta_1 + 2l\pi$, where an integer l is selected
3 such that each normalized phase $\tilde{\theta}_m$ is in a range of $[0, 2\pi)$.

1 10. The method of claim 1, in which the receiver is a cellular telephone.

1 11. A system for increasing transmit diversity gain in a wireless communication
2 system, comprising:
3 a receiver including one antenna, and further comprising:
4 means for measuring a phase of each of a plurality of signals
5 received by the one antenna;
6 means for selecting one of the plurality of signals as a reference
7 signal;
8 means for determining, independently for each other signal with
9 respect to the reference signal, feedback information indicating a required
10 rotation of each other signal so that a phase of each other signal is within an
11 identical quadrant as the phase of the reference signal; and
12 a transmitter with a plurality of antennas, and further comprising:
13 means for receiving the feedback information;
14 means for phase rotating each other signal according to the
15 corresponding feedback information to produce a rotated signal; and
16 means for transmitting the reference signal and each rotated signal to
17 the receiver.